

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ENOVALITE

Supplier's address: ENOVATEK GmbH, Sillensteder Straße 213, 26441 Jever, DE

Model identifier: ELED700108

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD5050		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	13	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 250 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P_{on}), expressed in W	13,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	2	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	100	
	Depth	5 000	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,440 0,403
Parameters for LED and OLED light sources:			
R9 colour rendering index value	80	Survival factor	-
the lumen maintenance factor	-		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,50	Colour consistency in McAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,4	Stroboscopic effect metric (SVM)	0,9

(a)-: not applicable;

(b)-: not applicable;

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.4288$ $y=0.3981/u'=0.2479$ $v'=0.5178$
 CCT=3093K(Duv=-0.0012) Dominant WL:Ld =582.9nm WL:Lc = --nm Purity=48.2%
 Ratio:R=22.8% G=74.2% B=3.0% Peak WL:Lp=606.6nm FWHM=129.8nm
 Render Index:Ra=84.6 AvgR=79.7 TM30:Rf=85 Rg=96

R1 =84 R2 =94 R3 =95 R4 =83 R5 =85 R6 =93 R7 =83
 R8 =61 R9 =14 R10=86 R11=83 R12=75 R13=87 R14=98 R15=77

Photo Parameters:

Flux = 1262 lm Eff. : 95.92 lm/W Fe = 3.871 W
 Scotopic:1803.5 S/P:1.429


Electrical parameters:

V = 11.998 V I = 1.097 A P = 13.16 W PF = 1.000
 LEVEL:OUT WHITE:ANSI_3000K
 Status: Integral T = 729 ms Ip = 32316 (49%)
 GBT5702

Model:ELED700108
 Tester:
 Temperature:25.3Deg
 Manufacturer:

Number:1
 Date:2023-06-09 14:38:39
 Humidity:65.0%
 Remarks:

Model placed on the Union market from 01/09/2023



EPREL registration number: 1630596

<https://eprel.ec.europa.eu/qr/1630596>

Supplier: ENOVATEK GmbH (Importer)

Website: www.enovatek.de

Customer care service:

Name: ENOVATEK GmbH

Website: www.enovatek.de

Email: info@enovatek.de

Phone: +49 4461 / 7464233

Address:

Sillensteder Straße 213

26441 Jever

Germany